



POLY DRUMS

For nearly 30 years, Eagle Manufacturing's ever-growing Poly Drum product line has handled both hazardous and non-hazardous storage needs for customers by offering Lab Packs, Overpacks, Open-Head and Salvage Drums. The 14- (53 L), 20- (75.7 L), 30- (113.6 L) and 55-gallon (208.2 L) Lab Packs and Open-Head Drums are available with plastic lids and a choice of metal or plastic lever locking rings. The 14- (53 L), 20- (75.7 L), 30- (113.6 L), 55- (208.2 L), 65- (246.1 L) and 95-gallon (359.6 L) Overpack and Salvage Drums are available with metal bands or screw-on lids. All models are constructed of chemical resistant, high-density polyethylene (HDPE) with UV inhibitors, are durable and lightweight and available in yellow, blue and black. All of our products are 100 percent made in the USA.

All drums feature:

- Blow-molded HDPE construction
- Chemical & weather resistant
- HDPE incinerates completely
- United Nations (UN) Certified to HM-181
- Operating temperature range (-40° F/-34° C to 140° F/54° C)
- Drop tested – max weight at 0° F/-17° C (48 hrs.)
- Approved for use with Packing Groups I, II and III
- UV Protection Package
- UL 94HB Flammability Rating
- Nestable for ideal storage (except model 1656)
- FDA 21 CFR 177.1520 Food Grade Quality
- Stack tested – three high at maximum weight capacity (24 hrs.)



Eagle drums are ideal for:

- Safe storage, handling and transportation of hazardous materials
- Spill containment and cleanup of hazardous materials
- Spill kit containers
- Original shipping containers
- Biowaste disposal and incineration



POLY DRUMS

10 GALLON DRUMS

	CLASSIC BAND			METAL BAND		BOLT BAND
Model Numbers	1609	1609BLK	1609B	1609M	1609MB	1609MBBR
Style	Lab Pack Open Head Drum	Lab Pack Open Head Drum	Lab Pack Open Head Drum	Lab Pack Open Head Drum	Lab Pack Open Head Drum	Lab Pack Open Head Drum
Closure Type	Plastic Band	Plastic Band	Plastic Band	Metal Band	Metal Band	Metal Bolt Ring
Inside Dimensions <small>Top: 14 1/8 in./35.9 cm. Bottom: 12 3/8 in./31.4 cm. Height: 18 in./45.7 cm.</small>	14 1/8 in./35.9 cm. 12 3/8 in./31.4 cm. 18 in./45.7 cm.	14 1/8 in./35.9 cm. 12 3/8 in./31.4 cm. 18 in./45.7 cm.	14 1/8 in./35.9 cm. 12 3/8 in./31.4 cm. 18 in./45.7 cm.	14 1/8 in./35.9 cm. 12 3/8 in./31.4 cm. 18 in./45.7 cm.	14 1/8 in./35.9 cm. 12 3/8 in./31.4 cm. 18 in./45.7 cm.	14 1/8 in./35.9 cm. 12 3/8 in./31.4 cm. 18 in./45.7 cm.
Outside Dimensions <small>Top: 15 in./38.1 cm. Bottom: 12 3/8 in./32.4 cm. Height: 18 1/8 in./46.5 cm.</small>	15 in./38.1 cm. 12 3/8 in./32.4 cm. 18 1/8 in./46.5 cm.	15 in./38.1 cm. 12 3/8 in./32.4 cm. 18 1/8 in./46.5 cm.	15 in./38.1 cm. 12 3/8 in./32.4 cm. 18 1/8 in./46.5 cm.	15 in./38.1 cm. 12 3/8 in./32.4 cm. 18 1/8 in./46.5 cm.	15 in./38.1 cm. 12 3/8 in./32.4 cm. 18 1/8 in./46.5 cm.	15 in./38.1 cm. 12 3/8 in./32.4 cm. 18 1/8 in./46.5 cm.
Maximum Capacity	133 lbs. 60 kg.	133 lbs. 60 kg.	133 lbs. 60 kg.	133 lbs. 60 kg.	133 lbs. 60 kg.	133 lbs. 60 kg.
Total Capacity	10 gal. 38 L	10 gal. 38 L	10 gal. 38 L	10 gal. 38 L	10 gal. 38 L	10 gal. 38 L
Maximum Container Size <small>(If used as an overpack drum)</small>	5 gal. 18.9 L	5 gal. 18.9 L	5 gal. 18.9 L	5 gal. 18.9 L	5 gal. 18.9 L	5 gal. 18.9 L
Weight	7.5 lbs. 3.4 kg.	7.5 lbs. 3.4 kg.	7.5 lbs. 3.4 kg.	7.5 lbs. 3.4 kg.	7.5 lbs. 3.4 kg.	7.5 lbs. 3.4 kg.
Pallet Quantity	81	81	81	81	81	81
Truckload Quantity	1,404	1,404	1,404	1,404	1,404	1,404
UN/DOT Rating	1H2/Y60/S	1H2/Y60/S	1H2/Y60/S	1H2/X60/S 1H2/Y75/S	1H2/X60/S 1H2/Y75/S	1H2/X60/S 1H2/Y75/S



Eagle 10-Gallon Poly Drum

Eagle's NEW 10 Gallon Lab Pack / Open Head Drum is blow molded with durable high-density polyethylene (HDPE) for maximum performance and quality. The HDPE is chemical and weather resistant and includes a UV protection package. Available in Yellow, Blue, Black or Natural HDPE, with plastic or metal lever lock, or metal bolt ring. 100 percent Made in the USA.

Features:

- Constructed of durable HDPE
- Nestable storage to optimize shipping and storage space
- Plastic or Metal Lever Locking Bands
- FDA 21 CFR 177.1520 Food Grade Quality
- Operating Temp range (-30° F to 130° F)
- Drop tested-max weight @ 0° F (48hrs)
- UL 94HB Flammability Rating

POLY DRUMS



14 GALLON DRUMS

20 GALLON DRUMS

BUNG LID / BOLT RING OPTIONS Available for some models

NEW! NATURAL COLORS Available for All Banded Drums



HDPE

100% Recyclable



Model Numbers <small>Bung Lid Models</small>	1610	1610BLK	1610M <small>1610MBGI</small>	1610MB <small>1610MBBGI</small>	1610MBLK <small>1610MBKBGI</small>	1652	1654	1623	1623BLK	1623M
Style	Lab Pack Open Head Drum	Lab Pack Open Head Drum	Lab Pack Open Head Drum	Lab Pack Open Head Drum	Lab Pack Open Head Drum	Lab Pack	Salvage Drum	Lab Pack Open Head Drum	Lab Pack Open Head Drum	Lab Pack Open Head Drum
Closure Type	Plastic Lever-Lock	Plastic Lever-Lock	Metal Lever-Lock	Metal Lever-Lock	Metal Lever-Lock	Plastic Lever-Lock	Metal Lever-Lock	Plastic Lever-Lock	Plastic Lever-Lock	Metal Lever-Lock
Inside Dimensions <small>Top: Bottom: Height:</small>	13½ in./34.3 cm. 12¾ in./31.4 cm. 25 in./63.5 cm.	13½ in./34.3 cm. 12¾ in./31.4 cm. 25 in./63.5 cm.	13½ in./34.3 cm. 12¾ in./31.4 cm. 25 in./63.5 cm.	13½ in./34.3 cm. 12¾ in./31.4 cm. 25 in./63.5 cm.	13½ in./34.3 cm. 12¾ in./31.4 cm. 25 in./63.5 cm.	19 in./48.3 cm. 16⅞ in./41.4 cm. 19 in./48.3 cm.	19 in./48.3 cm. 16⅞ in./41.4 cm. 19 in./48.3 cm.	15½ in./39 cm. 12⅞ in./32.7 cm. 29½ in./75.9 cm.	15½ in./39 cm. 12⅞ in./32.7 cm. 29½ in./75.9 cm.	15½ in./39 cm. 12⅞ in./32.7 cm. 29½ in./75.9 cm.
Outside Dimensions <small>Top: Bottom: Height:</small>	15 in./38.1 cm. 12¾ in./32.4 cm. 26½ in./67.3 cm.	15 in./38.1 cm. 12¾ in./32.4 cm. 26½ in./67.3 cm.	15 in./38.1 cm. 12¾ in./32.4 cm. 26½ in./67.3 cm.	15 in./38.1 cm. 12¾ in./32.4 cm. 26½ in./67.3 cm.	15 in./38.1 cm. 12¾ in./32.4 cm. 26½ in./67.3 cm.	20½ in./53 cm. 16⅞ in./42.4 cm. 20⅞ in./51.9 cm.	20½ in./53 cm. 16⅞ in./42.4 cm. 20⅞ in./51.9 cm.	15½ in./40 cm. 13¼ in./33.7 cm. 30½ in./77.5 cm.	15½ in./40 cm. 13¼ in./33.7 cm. 30½ in./77.5 cm.	15½ in./40 cm. 13¼ in./33.7 cm. 30½ in./77.5 cm.
Maximum Capacity	143 lbs. 65 kg.	143 lbs. 65 kg.	220 lbs. 100 kg.	220 lbs. 100 kg.	220 lbs. 100 kg.	88 lbs. 40 kg.	165 lbs. 75 kg.	220 lbs. 100 kg.	220 lbs. 100 kg.	220 lbs. 100 kg.
Total Capacity	14 gal. 52.2 L	14 gal. 52.2 L	14 gal. 52.2 L	14 gal. 52.2 L	14 gal. 52.2 L	20 gal. 77 L	20 gal. 77 L	20 gal. 77 L	20 gal. 77 L	20 gal. 77 L
Maximum Container Size <small>(If used as an overpack drum)</small>	5 gal. 18.9 L	5 gal. 18.9 L	5 gal. 18.9 L	5 gal. 18.9 L	5 gal. 18.9 L	5 gal. 18.9 L	5 gal. 18.9 L	5 gal. 18.9 L	5 gal. 18.9 L	5 gal. 18.9 L
Weight	9 lbs. 3.6 kg.	9 lbs. 3.6 kg.	10 lbs. 4.1 kg.	10 lbs. 4.1 kg.	10 lbs. 4.1 kg.	15 lbs. 5.85 kg.	16 lbs. 6.75 kg.	10.25 lbs. 4.65 kg.	10.25 lbs. 4.65 kg.	11.5 lbs. 5.2 kg.
Pallet Quantity	54	54	54	54	54	40	40	42	42	42
Truckload Quantity	1,404	1,404	1,404	1,404	1,404	1,000	1,000	1,092	1,092	1,092
UN/DOT Rating	1H2/X65/S 1H2/Y100/S	1H2/X65/S 1H2/Y100/S	1H2/X65/S 1H2/Y100/S	1H2/X65/S 1H2/Y100/S	1H2/X65/S 1H2/Y100/S	1H2/X40/S	1H2/X75/S	1H2/X75/S 1H2/Y100/S	1H2/X75/S 1H2/Y100/S	1H2/X75/S 1H2/Y100/S



Lab Packs/Open Head – for use with smaller non-damaged bottles, cans, carboys and 5-gallon (18.9 L) pails of non-leaking hazardous materials – if leaking, must pack with sufficient sorbents – NO FREE LIQUIDS.

Regulatory Compliance:
Lab Packs/Open Head: DOT 49 CFR 173.12 / Overpacks: DOT 49 CFR 173.25
Salvage Drums: DOT 49 CFR 173.3

Salvage Drums – for use with damaged or leaking containers of hazardous materials or used absorbent materials contaminated with a hazardous substance. Require “Salvage Drum” labeling and must pass a 3-PSI pressure test.

Overpacks – for use with larger non-damaged containers, cans and drums of non-leaking hazardous materials – if leaking, must pack with sufficient sorbents – NO FREE LIQUIDS.

UN Markings: UN 1H2/X340/S/96USA/M4990
1- Type of Container (drum), H-material of construction (plastic), 2- Removable head/X-Testing performance (X=Groups I, II, & III), 340-Max. Wt. of Container (Kg)S-solids/96/Year of Manufacture, USA-State Authorization Mark/M - certification compliance, 4990 -Testing Agency number.



POLY DRUMS



20 GALLON DRUMS

30 GALLON DRUMS

40 GALLON DRUMS

BUNG LID / BOLT RING OPTIONS Available for 30 Gallon Eagle Models

NEW! NATURAL COLORS Available for All Banded Drums



Model Numbers	1623MB	1623MBLK	1601	1601BLK 1601BLKBG	1601M 1601MBG2 or 1601BLKBRBG2	1601MB 1601MBBBG or 1601MBBG2	1601MBLK 1601MBLKBG or 1601MBKBG2	1602	1651	1651MB
Bung Lid Models									AVAILABLE IN BLACK 1651MBLK	
Style	Lab Pack Open Head Drum	Lab Pack Open Head Drum	Lab Pack Open Head Drum	Lab Pack Open Head Drum	Lab Pack Open Head Drum	Lab Pack Open Head Drum	Lab Pack Open Head Drum	Salvage Drum	Lab Pack Open Head Drum	Lab Pack Open Head Drum
Closure Type	Metal Lever-Lock	Metal Lever-Lock	Plastic Lever-Lock	Plastic Lever-Lock	Metal Lever-Lock	Metal Lever-Lock	Metal Lever-Lock	Metal Lever-Lock	Metal Lever-Lock	Metal Lever-Lock
Inside Dimensions	Top: 15½ in./39 cm. Bottom: 12¾ in./32.7 cm. Height: 29¾ in./75.9 cm.	Top: 15½ in./39 cm. Bottom: 12¾ in./32.7 cm. Height: 29¾ in./75.9 cm.	Top: 19 in./48.3 cm. Bottom: 16¼ in./41.3 cm. Height: 26¾ in./67 cm.	Top: 19 in./48.3 cm. Bottom: 16¼ in./41.3 cm. Height: 26¾ in./67 cm.	Top: 19 in./48.3 cm. Bottom: 16¼ in./41.3 cm. Height: 26¾ in./67 cm.	Top: 19 in./48.5 cm. Bottom: 16¼ in./41.3 cm. Height: 26¾ in./67 cm.	Top: 19 in./48.5 cm. Bottom: 16¼ in./41.3 cm. Height: 26¾ in./67 cm.	Top: 19 in./48.5 cm. Bottom: 16¼ in./41.3 cm. Height: 26¾ in./67 cm.	Top: 22¾ in./58.1 cm. Bottom: 18¾ in./48.3 cm. Height: 29¼ in./98 cm.	Top: 22¾ in./58.1 cm. Bottom: 19 in./48.3 cm. Height: 38¾ in./98 cm.
Outside Dimensions	Top: 15½ in./40 cm. Bottom: 13¼ in./33.7 cm. Height: 30¾ in./77.5 cm.	Top: 15½ in./40 cm. Bottom: 13¼ in./33.7 cm. Height: 30¾ in./77.5 cm.	Top: 21½ in./54 cm. Bottom: 16¾ in./42.2 cm. Height: 28½ in./72.4 cm.	Top: 21½ in./54 cm. Bottom: 16¾ in./42.2 cm. Height: 28½ in./72.4 cm.	Top: 21½ in./54 cm. Bottom: 16¾ in./42.2 cm. Height: 28½ in./72.4 cm.	Top: 21½ in./54 cm. Bottom: 16¾ in./42.2 cm. Height: 28½ in./72.4 cm.	Top: 21½ in./54 cm. Bottom: 16¾ in./42.2 cm. Height: 28½ in./72.4 cm.	Top: 21½ in./54 cm. Bottom: 16¾ in./42.2 cm. Height: 28½ in./72.4 cm.	Top: 23¾ in./60.3 cm. Bottom: 19¾ in./49.2 cm. Height: 30¾ in./99.4 cm.	Top: 23¾ in./60.3 cm. Bottom: 19¾ in./48.6 cm. Height: 30¾ in./77.2 cm.
Maximum Capacity	220 lbs. 100 kg.	220 lbs. 100 kg.	220 lbs. 100 kg.	220 lbs. 100 kg.	396 lbs. 180 kg.	396 lbs. 180 kg.	396 lbs. 180 kg.	396 lbs. 180 kg.	To Be Determined	To Be Determined
Total Capacity	20 gal. 77 L	20 gal. 77 L	30 gal. 114 L	30 gal. 114 L	30 gal. 114 L	30 gal. 114 L	30 gal. 114 L	30 gal. 114 L	40 gal. 151.4 L	40 gal. 151.4 L
Maximum Container Size (If used as an overpack drum)	5 gal. 18.9 L	5 gal. 18.9 L	16 gal. 60.6 L	16 gal. 60.6 L	16 gal. 60.6 L	16 gal. 60.6 L	16 gal. 60.6 L	16 gal. 60.6 L	30 gal. 113.6 L	30 gal. 113.6 L
Weight	11.5 lbs. 5.7 kg.	11.5 lbs. 5.2 kg.	16 lbs. 6.3 kg.	18 lbs. 7.2 kg.	18 lbs. 7.2 kg.	18 lbs. 7.2 kg.	18 lbs. 7.2 kg.	18 lbs. 7.2 kg.	17 lbs. 7.7 kg.	17 lbs. 7.7 kg.
Pallet Quantity	42	42	40	40	40	40	40	40	40	40
Truckload Quantity	1,092	1,092	1,000	1,000	1,000	1,000	1,000	1,000	1,000	1,000
UN/DOT Rating	1H2/X75/S 1H2/Y100/S	1H2/X75/S 1H2/Y100/S	1H2/X100/S 1H2/Y180/S	1H2/X100/S 1H2/Y180/S	1H2/X120/S 1H2/Y180/S	1H2/X120/S 1H2/Y180/S	1H2/X120/S 1H2/Y180/S	1H2/X120/S 1H2/Y180/S	To Be Determined	To Be Determined

Benefits of Blow-Molded HDPE Drums

HDPE is a very high molecular weight material, designed for an optimum balance of density, molecular weight and molecular weight distribution, demonstrating maximum property advantages for large products that require high impact resistance. Some of these advantages include:

- Environmental stress crack resistance (ESCR)
- Impact strength – even at a low temperature

- Flexural modulus – durability and resilience
- Chemical resistance – to wide range of chemicals
- Abrasion resistance – prevents gouging and scuffing
- Ultraviolet (UV) protection – superior blending process
- Plain Lid with gasket to seal lid to drum with drum lever ring (lever rings come in powder-coated metal or HDPE plastic)
- Lid with two 2 in. (5.08 cm.) bung lids for drum pump straight thread connections
- Lid with one 2 in. (5.08 cm.) and one 3/4 in. (1.9 cm.) bung lids for drum pump straight thread connections

Lid Styles:

- Lids feature closed cell foam or silicone gaskets
- Lid closure instructions included in each drum
- Salvage Drums pass 3-PSI pressure test

BOLT BAND W/
REGULAR LID
AVAILABLE IN
12 & 16 GAUGE

BUNG LID
2 BUNG HOLES:
ONE 2 IN. AND ONE ¾ IN. NTP

SCREW TOP

PLASTIC
LEVER-LOCK

METAL
LEVER-LOCK

METAL
BAND W/BOLT



POLY DRUMS



55 GALLON DRUMS

BUNG LID / BOLT RING OPTIONS Available for 55 Gallon Eagle Models

NEW! NATURAL COLORS Available for All Banded Drums



Model Numbers <small>Bung Lid Models</small>	1655	1655BLK	1655M <small>1655MBG</small>	1655MB <small>1655MBBG</small>	1655MBLK <small>1655MBLKBG</small>	1655MN <small>1655MNBG</small>	1656	1656BLK <small>1656BLKBG</small>	1656M <small>1656MBG2</small>	1656MB <small>1656MBBG2</small>	1656MBLK <small>1656MBLKBG or 1656MBLKBG2</small>
Style	Lab Pack Open Head Drum	Lab Pack Open Head Drum	Lab Pack Open Head Drum	Lab Pack Open Head Drum	Lab Pack Open Head Drum	Lab Pack Open Head Drum	Lab Pack Open Head Drum	Lab Pack Open Head Drum	Lab Pack Salvage Drum	Lab Pack	Lab Pack
Closure Type	Plastic Lever-Lock	Plastic Lever-Lock	Metal Lever-Lock	Metal Lever-Lock	Metal Lever-Lock	Metal Lever-Lock	Plastic Lever-Lock	Plastic Lever-Lock	Metal Lever-Lock	Metal Lever-Lock	Metal Lever-Lock
Inside Dimensions <small>Top: Bottom: Height:</small>	22 $\frac{1}{2}$ in./58.1 cm. 19 in./48.3 cm. 38 $\frac{5}{16}$ in./98 cm.	22 $\frac{1}{2}$ in./58.1 cm. 19 in./48.3 cm. 38 $\frac{5}{16}$ in./98 cm.	22 $\frac{1}{2}$ in./58.1 cm. 19 in./48.3 cm. 38 $\frac{5}{16}$ in./98 cm.	22 $\frac{1}{2}$ in./58.1 cm. 19 in./48.3 cm. 38 $\frac{5}{16}$ in./98 cm.	22 $\frac{1}{2}$ in./58.1 cm. 19 in./48.3 cm. 38 $\frac{5}{16}$ in./98 cm.	22 $\frac{1}{2}$ in./58.1 cm. 19 in./48.3 cm. 38 $\frac{5}{16}$ in./98 cm.	22 $\frac{1}{2}$ in./58.1 cm. 19 in./48.3 cm. 38 $\frac{5}{16}$ in./98 cm.	20 $\frac{1}{16}$ in./51.2 cm. 22 $\frac{1}{2}$ in./56.2 cm. 35 $\frac{13}{16}$ in./91 cm.	20 $\frac{1}{16}$ in./51.2 cm. 22 $\frac{1}{2}$ in./56.2 cm. 35 $\frac{13}{16}$ in./91 cm.	20 $\frac{1}{16}$ in./51.2 cm. 22 $\frac{1}{2}$ in./56.2 cm. 35 $\frac{13}{16}$ in./91 cm.	20 $\frac{1}{16}$ in./51.2 cm. 22 $\frac{1}{2}$ in./56.2 cm. 35 $\frac{13}{16}$ in./91 cm.
Outside Dimensions <small>Top: Bottom: Height:</small>	23 $\frac{3}{4}$ in./60.3 cm. 19 $\frac{1}{2}$ in./49.2 cm. 39 $\frac{1}{2}$ in./99.4 cm.	23 $\frac{3}{4}$ in./60.3 cm. 19 $\frac{1}{2}$ in./49.2 cm. 39 $\frac{1}{2}$ in./99.4 cm.	23 $\frac{3}{4}$ in./60.3 cm. 19 $\frac{1}{2}$ in./49.2 cm. 39 $\frac{1}{2}$ in./99.4 cm.	23 $\frac{3}{4}$ in./60.3 cm. 19 $\frac{1}{2}$ in./49.2 cm. 39 $\frac{1}{2}$ in./99.4 cm.	23 $\frac{3}{4}$ in./60.3 cm. 19 $\frac{1}{2}$ in./49.2 cm. 39 $\frac{1}{2}$ in./99.4 cm.	23 $\frac{3}{4}$ in./60.3 cm. 19 $\frac{1}{2}$ in./49.2 cm. 39 $\frac{1}{2}$ in./99.4 cm.	23 $\frac{3}{4}$ in./60.3 cm. 19 $\frac{1}{2}$ in./49.2 cm. 39 $\frac{1}{2}$ in./99.4 cm.	21 in./55.3 cm. 22 $\frac{1}{2}$ in./57.2 cm. 36 $\frac{1}{2}$ in./92.4 cm.	21 in./55.3 cm. 22 $\frac{1}{2}$ in./57.2 cm. 36 $\frac{1}{2}$ in./92.4 cm.	21 in./55.3 cm. 22 $\frac{1}{2}$ in./57.2 cm. 36 $\frac{1}{2}$ in./92.4 cm.	21 in./55.3 cm. 22 $\frac{1}{2}$ in./57.2 cm. 36 $\frac{1}{2}$ in./92.4 cm.
Maximum Capacity	220 lbs. 100 kg.	220 lbs. 100 kg.	551 lbs. 250 kg.	551 lbs. 250 kg.	551 lbs. 250 kg.	551 lbs. 250 kg.	220 lbs. 100 kg.	220 lbs. 100 kg.	551 lbs. 250 kg.	551 lbs. 250 kg.	551 lbs. 250 kg.
Total Capacity	55 gal. 212 L	55 gal. 212 L	55 gal. 212 L	55 gal. 212 L	55 gal. 212 L	55 gal. 212 L	55 gal. 217 L	55 gal. 217 L	55 gal. 217 L	55 gal. 217 L	55 gal. 217 L
Maximum Container Size <small>(If used as an overpack drum)</small>	30 gal. 113.6 L	30 gal. 113.6 L	30 gal. 113.6 L	30 gal. 113.6 L	30 gal. 113.6 L	30 gal. 113.6 L	30 gal. 113.6 L	30 gal. 113.6 L	30 gal. 113.6 L	30 gal. 113.6 L	30 gal. 113.6 L
Weight	23.5 lbs. 10.7 kg.	23.5 lbs. 10.7 kg.	23.5 lbs. 10.7 kg.	23.5 lbs. 10.7 kg.	23.5 lbs. 10.7 kg.	23.5 lbs. 10.7 kg.	23.5 lbs. 10.7 kg.	23.5 lbs. 10.7 kg.	23.5 lbs. 10.7 kg.	23.5 lbs. 10.7 kg.	23.5 lbs. 10.7 kg.
Pallet Quantity	36	36	36	36	36	36	8	8	8	8	8
Truckload Quantity	864	864	864	864	864	864	336 Not Palletized	336 Not Palletized	336 Not Palletized	336 Not Palletized	336 Not Palletized
UN/DOT Rating	1H2/X65/S 1H2/Y100/S	1H2/X65/S 1H2/Y100/S	1H2/X200/S 1H2/Y250/S	1H2/X200/S 1H2/Y250/S	1H2/X200/S 1H2/Y250/S	1H2/X200/S 1H2/Y250/S	1H2/X100/S 1H2/Y100/S	1H2/X100/S 1H2/Y100/S	1H2/X200/S 1H2/Y250/S	1H2/X200/S 1H2/Y250/S	1H2/X200/S 1H2/Y250/S



Did you know?

Eagle HDPE poly drums with screw tops or plastic lever-lock lid closures can be incinerated completely.

Lab Packs/Open Head

— for use with smaller non-damaged bottles, cans, carboys and 5-gallon (18.9 L) pails of non-leaking hazardous materials — if leaking, must pack with sufficient sorbents — NO FREE LIQUIDS.

Salvage Drums

— for use with damaged or leaking containers of hazardous materials or used absorbent materials contaminated with a hazardous substance. Require “Salvage Drum” labeling and must pass a 3-PSI pressure test.

Overpacks

— for use with larger non-damaged containers, cans and drums of non-leaking hazardous materials — if leaking, must pack with sufficient sorbents for — NO FREE LIQUIDS.

Regulatory Compliance:

Lab Packs/Open Head: DOT 49 CFR 173.12
Overpacks: DOT 49 CFR 173.25
Salvage Drums: DOT 49 CFR 173.3

POLY DRUMS



SCREW-TOP DRUMS

SALVAGE DRUMS

AVAILABLE IN BROWN
1600SLBRN



HDPE

100% Recyclable



Model Numbers
Lid Model Numbers

1650

1600SL

1657

1661

1690

1665

1695

Style

Lab Pack

Lab Pack

Lab Pack

Overpack

Overpack

Salvage Drum

Salvage Drum

Closure Type

Screw-on lid

Screw-on lid

Screw-on lid

Screw-on lid

Screw-on lid

Metal band w/bolt

Metal band w/bolt

Inside Dimensions

Top:
Bottom:
Height:

19¹/₂ in./49.3 cm.
16³/₈ in./41.6 cm.
20 in./50.8 cm.

19¹/₂ in./50.5 cm.
16¹/₂ in./41.3 cm.
27 in./68.6 cm.

23¹/₂ in./60.7 cm.
19 in./48.3 cm.
39¹/₄ in./99.7 cm.

27¹/₂ in./68.9 cm.
25⁵/₁₆ in./65.9 cm.
31¹/₄ in./79.4 cm.

27¹/₂ in./68.9 cm.
25⁵/₁₆ in./65 cm.
39 in./99.1 cm.

27¹/₂ in./68.9 cm.
25¹/₂ in./64.8 cm.
35¹/₂ in./91.2 cm.

27¹/₂ in./69.9 cm.
25¹/₄ in./64.2 cm.
38 in./96.6 cm.

Outside Dimensions

Top:
Bottom:
Height:

20³/₈ in./51.8 cm.
16³/₈ in./42.6 cm.
20³/₄ in./52.7 cm.

22¹/₂ in./57.2 cm.
16³/₈ in./42.3 cm.
28¹/₄ in./71.8 cm.

26¹/₂ in./67.4 cm.
19¹/₂ in./49.3 cm.
40 in./101.6 cm.

31 in./78.8 cm.
26⁷/₁₆ in./67.2 cm.
33¹/₄ in./85.8 cm.

31 in./78.8 cm.
26⁷/₁₆ in./66.2 cm.
41¹/₄ in./104.8 cm.

31 in./78.8 cm.
26 in./66.1 cm.
38¹/₂ in./98.8 cm.

31 in./78.8 cm.
25³/₄ in./65.4 cm.
44¹/₂ in./112.8 cm.

Maximum Capacity

125 lbs.
57 kg.

396 lbs.
180 kg.

551 lbs.
250 kg.

660 lbs.
300 kg.

660 lbs.
300 kg.

440 lbs.
200 kg.

748 lbs.
340 kg.

Total Capacity

20 gal.
76 L

30 gal.
114 L

55 gal.
217 L

65 gal.
247 L

95 gal.
361 L

65 gal.
247 L

95 gal.
361 L

Maximum Container Size
(If used as an overpack drum)

5 gal.
18.9 L

16 gal.
60.6 L

30 gal.
113.6 L

30 gal.
113.6 L

55 gal.
208.2 L

55 gal.
208.2 L

55 gal.
208.2 L

Weight

13 lbs.
5.85 kg.

18 lbs.
6.3 kg.

28 lbs.
6.3 kg.

45 lbs.
20.25 kg.

50 lbs.
22.5 kg.

53 lbs.
23.85 kg.

58 lbs.
26.1 kg.

Pallet Quantity

24

24

5

3

3

4

4

Truckload Quantity

528

720

332

180

180

192

192

UN/DOT Rating

1H2/X57/S

1H2/X120/S
1H2/Y180/S

1H2/X200/S
1H2/Y250/S

1H2/X300/S

1H2/X300/S

1H2/X200/S

1H2/X340/S



SCREW TOP



METAL BAND W/BOLT



Model 1609



UN Markings: UN 1H2/X340/S/96USA/M4990
1- Type of Container (drum), H-material of construction (plastic), 2-Removable head/X-Testing performance (X=Groups I, II, & III), 340-Max. Wt. of Container (Kg)/S-solids/96/Year of Manufacture, USA-State Authorization Mark/M - certification compliance, 4990-Testing Agency number.