



# SAFETY CANS



## SIMPLY CANTASTIC!

Baked-on Powder Coat Finish + 100 Percent Leak Tested!

Featuring Environmentally Friendly Hot Dipped 24-Gauge Galvanized Steel

Patented Comfort Grip Trigger Release

Spring Closing Lid With Nitrile Gasket That Vents at 5-PSI Internal Pressure

Fixed Handle

Non-Sparking Flame Arrestor and Pour Spout

Baked-on Powder Coat Finish

Available in 1- (3.8 L), 2- (7.6 L), 2.5- (9.5 L) & 5-Gallon (18.9 L) Sizes

Meet OSHA & NFPA Code 30 Requirements

FM, UL & ULC Approved

Accepted Under CARB

Double Interlock No-Weld Bottom Seam



Optional F15 HDPE Funnel Fits Unleaded Fuel Tanks

The Only Deep Drawn Seamless Can Made

Deep Drawn Construction Means No Top or Side Seam

Trilingual Label

Model UI50FS 12½ in. (31.8 cm.) x 13½ in. (34.3 cm.)

# SAFETY CANS


For nearly 60 years, our Safety Can product line has been an industry leader of galvanized Type I and Type II Safety Cans that meet OSHA and NFPA Code 30 requirements, and are UL and ULC listed and FM Approved for safe storage and handling of flammable liquids. Eagle offers FM Approved Compliance Solutions in a variety of poly and stainless cans, lab cans, faucet cans, disposal cans, plunger, bench & daub cans, and poly oily waste cans to help keep your personnel and facilities protected. Made in the USA.

### Safety Can options:

- Type I Safety Cans
- Type II Safety Cans
- Type I Poly Cans
- Stainless Cans
- Lab Cans
- Faucet Cans
- DOT Cans
- Disposal Cans
- Specialty Cans
- Plunger Cans
- Bench Cans
- Daub Cans
- Poly Oily Waste Cans
- Biohazardous Cans



Patented comfort grip trigger release plus spring closing lid with nitrile gasket that vents at 5-PSI internal pressure



Double interlock no-weld bottom seam is the only deep drawn seamless can made



FLAMMABLE



DIESEL



KEROSENE

# SAFETY CANS



## TYPE I SAFETY CANS

FLAMMABLES	TYPE I SAFETY CANS				
<b>Model Numbers</b>	<b>UI4S</b>	<b>UI10S</b>	<b>UI20S</b>	<b>UI25S*</b>	<b>UI50S</b>
<b>Model-w/Funnel</b>	<b>UI4FS</b>	<b>UI10FS</b>	<b>UI20FS</b>	<b>UI25FS*</b>	<b>UI50FS</b>
<b>Capacity</b>	2 qt./2 L	1 gal./3.8 L	2 gal./7.6 L	2½ gal./9.5 L	5 gal./18.9 L
<b>Dimensions</b> <small>Diameter Height</small>	9 in./22.9 cm. 5½ in./13.5 cm.	9 in./22.9 cm. 8 in./20.4 cm.	11¼ in./28.6 cm. 9½ in./24.2 cm.	11¼ in./28.6 cm. 10 in./25.4 cm.	12½ in./31.8 cm. 13½ in./34.3 cm.
<b>Weight</b>	2.25 lbs./1.1 kg.	3.52 lbs./1.6 kg.	5.25 lbs./2.4 kg.	5.7 lbs./2.6 kg.	7 lbs./3.2 kg.
<b>Construction</b>	<b>Galvanized</b>	<b>Galvanized</b>	<b>Galvanized</b>	<b>Galvanized</b>	<b>Galvanized</b>

## TYPE I SAFETY CANS

DIESEL	TYPE I SAFETY CANS				
<b>Model Numbers</b>	<b>UI4SY</b>	<b>UI10SY</b>	<b>UI20SY</b>	<b>UI25SY*</b>	<b>UI50SY</b>
<b>Model-w/Funnel</b>	<b>UI4FSY</b>	<b>UI10FSY</b>	<b>UI20FSY</b>	<b>UI25FSY*</b>	<b>UI50FSY</b>
<b>Capacity</b>	2 qt./2 L	1 gal./3.8 L	2 gal./7.6 L	2½ gal./9.5 L	5 gal./18.9 L
<b>Dimensions</b> <small>Diameter Height</small>	9 in./22.9 cm. 5½ in./13.5 cm.	9 in./22.9 cm. 8 in./20.4 cm.	11¼ in./28.6 cm. 9½ in./24.2 cm.	11¼ in./28.6 cm. 10 in./25.4 cm.	12½ in./31.8 cm. 13½ in./34.3 cm.
<b>Weight</b>	2.25 lbs./1.1 kg.	3.52 lbs./1.6 kg.	5.25 lbs./2.4 kg.	5.7 lbs./2.6 kg.	7 lbs./3.2 kg.
<b>Construction</b>	<b>Galvanized</b>	<b>Galvanized</b>	<b>Galvanized</b>	<b>Galvanized</b>	<b>Galvanized</b>

### Type I Safety Cans

- Eagle Type 1 Safety Cans are constructed of 24-gauge hot dipped galvanized steel, whereas other manufacturers' safety cans use lead-coated terne steel
- These safety cans are accepted under CARB, meet OSHA and NFPA Code 30 requirements, and are UL, ULC and FM Approved for safe handling and storage of gasoline and other flammable liquids
- Available in a variety of colors for the safe handling and storage of kerosene (blue), diesel (yellow) and combustible liquids such as oils (green)

\* Meets the New York City Fire Code Title 29 FC 2204.4.4.1.1 Maximum 2.5 gallon (9.5 L) container regulations

Compliance: OSHA 29 CFR 1910.106, 1926.152 and NFPA Code 30



## TYPE I SAFETY CANS

KEROSENE	TYPE I SAFETY CANS				
<b>Model Numbers</b>	<b>UI4SB</b>	<b>UI10SB</b>	<b>UI20SB</b>	<b>UI25SB*</b>	<b>UI50SB</b>
<b>Model-w/Funnel</b>	<b>UI4FSB</b>	<b>UI10FSB</b>	<b>UI20FSB</b>	<b>UI25FSB*</b>	<b>UI50FSB</b>
<b>Capacity</b>	2 qt./2 L	1 gal./3.8 L	2 gal./7.6 L	2½ gal./9.5 L	5 gal./18.9 L
<b>Dimensions</b> <small>Diameter Height</small>	9 in./22.9 cm. 5½ in./13.5 cm.	9 in./22.9 cm. 8 in./20.4 cm.	11¼ in./28.6 cm. 9½ in./24.2 cm.	11¼ in./28.6 cm. 10 in./25.4 cm.	12½ in./31.8 cm. 13½ in./34.3 cm.
<b>Weight</b>	2.25 lbs./1.1 kg.	3.52 lbs./1.6 kg.	5.25 lbs./2.4 kg.	5.7 lbs./2.6 kg.	7 lbs./3.2 kg.
<b>Construction</b>	<b>Galvanized</b>	<b>Galvanized</b>	<b>Galvanized</b>	<b>Galvanized</b>	<b>Galvanized</b>

## TYPE I SAFETY CANS

COMBUSTIBLES	TYPE I SAFETY CANS				
<b>Model Numbers</b>	<b>UI4SG</b>	<b>UI10SG</b>	<b>UI20SG</b>	<b>UI25SG*</b>	<b>UI50SG</b>
<b>Model-w/Funnel</b>	<b>UI4FSG</b>	<b>UI10FSG</b>	<b>UI20FSG</b>	<b>UI25FSG*</b>	<b>UI50FSG</b>
<b>Capacity</b>	2 qt./2 L	1 gal./3.8 L	2 gal./7.6 L	2½ gal./9.5 L	5 gal./18.9 L
<b>Dimensions</b> <small>Diameter Height</small>	9 in./22.9 cm. 5½ in./13.5 cm.	9 in./22.9 cm. 8 in./20.4 cm.	11¼ in./28.6 cm. 9½ in./24.2 cm.	11¼ in./28.6 cm. 10 in./25.4 cm.	12½ in./31.8 cm. 13½ in./34.3 cm.
<b>Weight</b>	2.25 lbs./1.1 kg.	3.52 lbs./1.6 kg.	5.25 lbs./2.4 kg.	5.7 lbs./2.6 kg.	7 lbs./3.2 kg.
<b>Construction</b>	<b>Galvanized</b>	<b>Galvanized</b>	<b>Galvanized</b>	<b>Galvanized</b>	<b>Galvanized</b>

## TYPE I POLY CANS

	TYPE I POLY CANS						TYPE I STAINLESS STEEL CANS	
<b>Model Numbers</b>	<b>14169</b>	<b>14545</b>	<b>14261</b>	<b>14561</b>	<b>14535</b>	<b>14540</b>	<b>1313</b>	<b>1315</b>
<b>Capacity</b>	1 gal./4 L	5 gal./19 L	2.5 gal./9.5 L	5 gal./19 L	5 gal./19 L	5 gal./19 L	2½ gal./9.5 L	5 gal./19 L
<b>Dimensions</b> <small>Diameter Height</small>	7¼ in./184 mm. 11½ in./292 mm.	11½ in./292 mm. 17 in./432 mm.	10¼ in./273 mm. 14¼ in./362 mm.	12¼ in./324 mm. 16 in./406 mm.	11½ in./292 mm. 17 in./432 mm.	11½ in./292 mm. 17 in./432 mm.	11¼ in./28.6 cm. 9½ in./24.5 cm.	11¼ in./28.6 cm. 15¼ in./39.7 cm.
<b>Weight</b>	3 lbs./1 kg.	10 lbs./4 kg.	4 lbs./2 kg.	9 lbs./4 kg.	16 lbs./7 kg.	10 lbs./4 kg.	8 lbs./3.7 kg.	10 lbs./4.6 kg.
<b>Construction</b>	<b>Poly</b>	<b>Poly</b>	<b>Poly</b>	<b>Poly</b>	<b>Poly</b>	<b>Poly</b>	<b>Stainless</b>	<b>Stainless</b>

# SAFETY CANS



## TYPE II SAFETY CANS

	FLAMMABLES	KEROSENE	DIESEL	COMBUSTIBLES
<b>Model 7/8" Spout</b>	U226S	U251S	U226SB	U251SB
<b>Model 5/8" Spout</b>	U226SX5	U251SX5	U226SX5B	U251SX5B
<b>Capacity</b>	2½ gal./9.5 L	5 gal./19 L	2½ gal./9.5 L	5 gal./19 L
<b>Dimensions</b> Diameter Height	11¼ in./28.6 cm. 9½ in./24.2 cm.	12½ in./31.8 cm. 15½ in./40.4 cm.	11¼ in./28.6 cm. 9½ in./24.2 cm.	12½ in./31.8 cm. 15½ in./40.4 cm.
<b>Weight</b>	8 lbs./3.7 kg.	10 lbs./4.6 kg.	8 lbs./3.7 kg.	10 lbs./4.6 kg.
<b>Construction</b>	Galvanized	Galvanized	Galvanized	Galvanized

	FLAMMABLES	KEROSENE	DIESEL	COMBUSTIBLES
<b>Model 7/8" Spout</b>	U211S	U211SB	U211SY	U211SG
<b>Model 5/8" Spout</b>	U211SX5	U211SX5B	U211SX5Y	U211SX5G
<b>Capacity</b>	1 gal./3.8 L	1 gal./3.8 L	1 gal./3.8 L	1 gal./3.8 L
<b>Dimensions</b> Diameter Height	11¼ in./28.6 cm. 7¼ in./18.4 cm.	11¼ in./28.6 cm. 7¼ in./18.4 cm.	11¼ in./28.6 cm. 7¼ in./18.4 cm.	11¼ in./28.6 cm. 7¼ in./18.4 cm.
<b>Weight</b>	7 lbs./3.2 kg.	7 lbs./3.2 kg.	7 lbs./3.2 kg.	7 lbs./3.2 kg.
<b>Construction</b>	Galvanized	Galvanized	Galvanized	Galvanized

- Eagle Type II Safety Cans are made of galvanized steel and help reduce the danger of explosion while dispensing flammable liquids through a flexible 12 in. (30.5 cm.) metal spout
- Flame arrestors in filler opening and pour spout

Compliance: OSHA 29 CFR 1910.106, 1926.152 and NFPA Code 30



- Metal Safety Cans are FM, UL and ULC Approved and meet OSHA and NFPA Code 30 requirements. Poly Cans are FM Approved.



## STAINLESS

## POLY

<b>Model Numbers</b>	1301	12162	14065
<b>Approvals</b>			—
<b>Capacity</b>	1 gal./3.8 L	1 gal./4 L	½ gal./2 L
<b>Dimensions</b> Width Depth Height	4¼ in./10.8 cm. 8 in./20.4 cm. 13 in./33.1 cm.	4¾ in./117 mm. 7 in./194 mm. 12¼ in./324 mm.	4¾ in./117 mm. 7 in./194 mm. 9½ in./241 mm.
<b>Weight</b>	3.75 lbs./1.7 kg.	2 lbs./1 kg.	2 lbs./1 kg.
<b>Construction</b>	Stainless	Poly	Poly

## FAUCET CANS

## DOT CANS

<b>Model Numbers</b>	1417	1327	1215	1215SX5	1215Y	1215YSX5
<b>Approvals</b>			—	—	—	—
<b>Capacity</b>	5 gal./19 L	5 gal./19 L	5 gal./19 L	5 gal./19 L	5 gal./19 L	5 gal./19 L
<b>Dimensions</b> Diameter Height	12½ in./31.8 cm. 13½ in./34.3 cm.	11 in./28.6 cm. 15½ in./40.4 cm.	12½ in./31.8 cm. 15¾ in./40 cm.	12½ in./31.8 cm. 15¾ in./40 cm.	12 in./31.8 cm. 15¾ in./40 cm.	12½ in./31.8 cm. 15¾ in./40 cm.
<b>Weight</b>	12 lbs./5.5 kg.	9 lbs./4.1 kg.	13 lbs./5.9 kg.	13 lbs./5.9 kg.	13 lbs./5.9 kg.	13 lbs./5.9 kg.
<b>Construction</b>	Galvanized	Stainless	Galvanized	Galvanized	Galvanized	Galvanized

### Laboratory Safety Cans:

- Laboratory Safety Cans reduce the danger of explosions resulting from the ignition of vapors of flammable liquids
- Cans are available in coated metal, stainless steel and high-density polyethylene for safe storage and handling of most chemical compounds

Compliance: OSHA 29 CFR 1910.106, 1925.152 & NFPA Code 30

### DOT Transport Type II Safety Cans:






- Reduce the danger of explosion while dispensing flammable liquids through a flexible metal spout
- Have double-walled flame arrestors in filler opening and pour spout
- Heavy duty roll bars protect both spouts, and a thumb screw mechanism assures the filler opening stays closed while being transported
- Meet DOT requirements

Compliance: OSHA 29 CFR 1910.106, 1925.152 & NFPA Code 30 - UN/DOT-1A1/Y1.2/100/08/USA/M4990/0.6mm




















# SAFETY CANS



## DISPOSAL CANS





						
<b>Model Numbers</b>	<b>14762</b>	<b>14765</b>	<b>12751</b>	<b>12754</b>	<b>14565</b>	<b>12772</b>
<b>Approvals</b>						
<b>Capacity</b>	2 gal./7.5 L	5 gal./19 L	2 gal./7.5 L	5 gal./19 L	5 gal./19 L	5 gal./19 L
<b>Dimensions</b> <small>Diameter Height</small>	12 in./305 mm. 14 3/4 in./375 mm.	12 in./305 mm. 20 in./508 mm.	12 in./305 mm. 14 3/4 in./375 mm.	12 in./305 mm. 20 in./508 mm.	12 in./305 mm. 20 in./508 mm.	12 in./305 mm. 20 in./508 mm.
<b>Weight</b>	7 lbs./3 kg.	11 lbs./5 kg.	7 lbs./3 kg.	11 lbs./5 kg.	11 lbs./5 kg.	12 lbs./6 kg.
<b>Construction</b>	<b>Poly</b>	<b>Poly</b>	<b>Poly</b>	<b>Poly</b>	<b>Poly</b>	<b>Poly</b>

## PLUNGER CANS















	<b>METAL</b>			<b>POLY</b>		
						
<b>Model Numbers</b>	<b>P701</b> 	<b>P702</b> 	<b>P704</b> 	<b>P711</b> 	<b>P712</b> 	<b>P714</b> 
<b>Approvals</b>						
<b>Capacity</b>	1 qt./1 L	2 qt./1.9 L	4 qt./3.8 L	1 qt./1 L	2 qt./1.9 L	4 qt./3.8 L
<b>Dimensions</b> <small>Diameter Height</small>	6 1/4 in./15.9 cm. 8 in./20.4 cm.	8 in./20.4 cm. 8 1/2 in./21.6 cm.	8 in./20.4 cm. 10 1/4 in./27.3 cm.	5 1/4 in./13.4 cm. 9 1/4 in./24.8 cm.	6 1/2 in./16.6 cm. 11 in./28 cm.	7 1/4 in./19.7 cm. 13 in./33 cm.
<b>Weight</b>	2.34 lbs./1.1 kg.	3 lbs./1.4 kg.	3.67 lbs./1.7 kg.	2 lbs./0.9 kg.	3 lbs./1.4 kg.	4 lbs./1.9 kg.
<b>Construction</b>	<b>Galvanized</b>	<b>Galvanized</b>	<b>Galvanized</b>	<b>Poly</b>	<b>Poly</b>	<b>Poly</b>

## DISPOSAL CANS

## SPECIAL CANS

						
<b>Model Numbers</b>	<b>1423</b> 	<b>1425</b> 	<b>1323</b> 	<b>1325</b> 	<b>605</b> Lift Oil Can	<b>211</b> Tallow Pot
<b>Approvals</b>					-	-
<b>Capacity</b>	2 1/2 gal./9.5 L	5 gal./19 L	2 1/2 gal./9.5 L	5 gal./19 L	5 gal./19 L	4 pt./3.4 L
<b>Dimensions</b> <small>Diameter Height</small>	11 1/4 in./28.6 cm. 12 in./30.5 cm.	11 1/4 in./28.6 cm. 18 in./45.8 cm.	11 1/4 in./28.6 cm. 12 in./30.5 cm.	11 1/4 in./28.6 cm. 18 in./45.8 cm.	11 1/4 in./28.6 cm. 38 in./96.6 cm.	5 1/4 in./13.3 cm. 7 1/2 in./19 cm.
<b>Weight</b>	8 lbs./3.7 kg.	10 lbs./4.6 kg.	8 lbs./3.7 kg.	10 lbs./4.6 kg.	10 lbs./4.6 kg.	2 lbs./0.9 kg.
<b>Construction</b>	<b>Galvanized</b>	<b>Galvanized</b>	<b>Stainless</b>	<b>Stainless</b>	<b>Galvanized</b>	<b>Coated Metal</b>

## BENCH & DAUB CANS

	<b>DAUB</b>				<b>BENCH</b>			
								
<b>Model Numbers</b>	<b>B600D</b>	<b>B601</b>	<b>B602</b>	<b>B604</b>	<b>B606</b>	<b>B606NL</b>	<b>B608</b>	
<b>Approvals</b>								
<b>Capacity</b>	1/2 pt./0.2 L	1 qt./1 L	2 qt./1.9 L	4 qt./3.8 L	6 qt./5.7 L	6 qt./5.7 L	8 qt./7.6 L	
<b>Dimensions</b> <small>Diameter Height</small>	4 in./10.8 cm. 3 1/2 in./8.9 cm.	6 1/4 in./15.9 cm. 3 3/4 in./9.2 cm.	8 in./20.4 cm. 4 1/4 in./10.8 cm.	8 in./20.4 cm. 6 1/2 in./16.6 cm.	7 1/4 in./19.7 cm. 9 1/4 in./24.2 cm.	7 1/4 in./19.7 cm. 9 1/4 in./24.2 cm.	11 1/4 in./28.6 cm. 7 in./17.8 cm.	
<b>Weight</b>	1 lb./0.5 kg.	2.17 lbs./1 kg.	3 lbs./1.4 kg.	3.5 lbs./1.6 kg.	3.67 lbs./1.7 kg.	3.67 lbs./1.7 kg.	8.25 lbs./3.8 kg.	
<b>Construction</b>	<b>Galvanized</b>	<b>Galvanized</b>	<b>Galvanized</b>	<b>Galvanized</b>	<b>Galvanized</b>	<b>Galvanized</b>	<b>Galvanized</b>	

Optional cleaning basket shown is available for both models

### Metal & Polyethylene Disposal Safety Cans:

- Disposal Safety Cans provide an intermediate station for temporary storage of liquid wastes
- Spout cap opens to a wide 80° angle and can be locked open for conveniently emptying various types of containers
- Cans are equipped with a flame arrestor
- Cap assembly opens automatically to relieve excessive internal vapor pressures
- FM Approved



### Plunger & Bench Safety Cans:

- Eagle Safety Plunger Cans are ideal for cleaning with flammable or volatile fluids
- Feature flame arrestor dasher screens, brass pump assemblies, and comply with OSHA standards
- When the dasher plate is pushed down, the safety can dispenses a small amount of liquid to easily moisten sponges or rags without messy or dangerous spills
- Polyethylene and coated metal models available
- FM Approved
- Eagle Safety Bench Cans are designed for safer cleaning of small parts or swabbing of larger ones
- Dasher screens act as a fire baffle

## POLY WASTE CANS

<b>Model Numbers</b>	933FL	935FL	937FL	933FLY	935FLY	937FLY
<b>Approvals</b>						
<b>Capacity</b>	6 gal./22.8 L	10 gal./37.9 L	14 gal./53 L	6 gal./22.8 L	10 gal./37.9 L	14 gal./53 L
<b>Dimensions</b>	Width: 16½ in./42 cm. Depth: 13½ in./34.3 cm. Height: 16 in./40.7 cm.	22 in./55.9 cm. 18 in./45.8 cm. 18 in./45.8 cm.	22 in./55.9 cm. 18 in./45.8 cm. 21 in./53.4 cm.	16½ in./42 cm. 13½ in./34.3 cm. 16 in./40.7 cm.	22 in./55.9 cm. 18 in./45.8 cm. 18 in./45.8 cm.	22 in./55.9 cm. 18 in./45.8 cm. 21 in./53.4 cm.
<b>Weight</b>	9 lbs./4.1 kg.	14 lbs./6.4 kg.	16 lbs./7.3 kg.	9 lbs./4.1 kg.	14 lbs./6.4 kg.	16 lbs./7.3 kg.

## POLY WASTE CANS

## BIOHAZARDOUS POLY WASTE CANS

<b>Model Numbers</b>	933FLBK	935FLBK	937FLBK	943BIO	945BIO	947BIO
<b>Approvals</b>						
<b>Capacity</b>	6 gal./22.8 L	10 gal./37.9 L	14 gal./53 L	6 gal./22.8 L	10 gal./37.9 L	14 gal./53 L
<b>Dimensions</b>	Width: 16½ in./42 cm. Depth: 13½ in./34.3 cm. Height: 16 in./40.7 cm.	22 in./55.9 cm. 18 in./45.8 cm. 18 in./45.8 cm.	22 in./55.9 cm. 18 in./45.8 cm. 21 in./53.4 cm.	16½ in./42 cm. 13½ in./34.3 cm. 16 in./40.7 cm.	22 in./55.9 cm. 18 in./45.8 cm. 18 in./45.8 cm.	22 in./55.9 cm. 18 in./45.8 cm. 21 in./53.4 cm.
<b>Weight</b>	9 lbs./4.1 kg.	14 lbs./6.4 kg.	16 lbs./7.3 kg.	9 lbs./4.1 kg.	14 lbs./6.4 kg.	16 lbs./7.3 kg.

### Polyethylene Oily Waste Cans:

- Fire-safe temporary storage of solvent rags, waste rags, shavings and other materials

Compliance: OSHA 29 CFR 1910.125(e)(4)(ii) and OSHA 29 CFR 1910.125(e)(4)(iii)

### Polyethylene Biohazardous Waste Cans:

- Advise workers of potential biohazards and meet OSHA requirements for exposures to blood borne pathogens

Compliance: OSHA 29 CFR 1910.1030



## SAFESMOKER™ & Butt Cans

**SAFESMOKER™ Cigarette Receptacle** is made of high-density polyethylene with UV inhibitors, with a galvanized steel collection bucket inside. Design restricts oxygen to quickly extinguish burning butts. Top of container removes easily to access and empty internal bucket. Rain-protective design keeps water out and eliminates odor. Includes integrated hold-down tabs for security and wind protection.

**Eagle Butt Cans** are ideal for "designated smoking areas" inside or outside. Features poly tube and galvanized can base. Yellow for in-plant use and beige for office or commercial areas.

**Original Butt Cans** This all-metal galvanized steel can is excellent for smoking areas in industrial settings. 5-gallon (18.9 L) capacity in yellow or beige.



Model	Description	SafeSmoker™ Cigarette Receptacle Dimensions (dia. x height)	Capacity	Weight
1208BEIGE	SafeSmoker™-Beige	in: 17¼ x 43¼ cm: 43.8 x 109.9	4 gal./15.2 L	10 lbs./4.5 kg.
1208BROWN	SafeSmoker™-Brown	in: 17¼ x 43¼ cm: 43.8 x 109.9	4 gal./15.2 L	10 lbs./4.5 kg.
1208GRAY	SafeSmoker™-Gray	in: 17¼ x 43¼ cm: 43.8 x 109.9	4 gal./15.2 L	10 lbs./4.5 kg.
1208BLACK	SafeSmoker™-Black	in: 17¼ x 43¼ cm: 43.8 x 109.9	4 gal./15.2 L	10 lbs./4.5 kg.
1206BEIGE	SafeSmoker™-Beige	in: 15¼ x 37¼ cm: 38.8 x 95.9	5 qt./4.7 L	7 lbs./3.2 kg.
1206BROWN	SafeSmoker™-Brown	in: 15¼ x 37¼ cm: 38.8 x 95.9	5 qt./4.7 L	7 lbs./3.2 kg.
1206GRAY	SafeSmoker™-Gray	in: 15¼ x 37¼ cm: 38.8 x 95.9	5 qt./4.7 L	7 lbs./3.2 kg.
1206BLACK	SafeSmoker™-Black	in: 15¼ x 37¼ cm: 38.8 x 95.9	5 qt./4.7 L	7 lbs./3.2 kg.

### SHIPPING SIZES:

Model	Dimensions (L x W x H)
1200	in: 13 x 13 x 20 cm: 33.1 x 33.1 x 50.8
1202	in: 13 x 13 x 28 cm: 33.1 x 33.1 x 71.2
1205	in: 13 x 13 x 28 cm: 33.1 x 33.1 x 71.2
1206	in: 16 x 16 x 21 cm: 40.7 x 40.7 x 53.4
1208	in: 17½ x 17½ x 25 cm: 44.5 x 44.5 x 63.5

All cans are FM Approved.

Capacity	Dimensions	Metal/Poly Butt Cans			Weight
		Yellow	Beige	Black	
2 gal./7.58 L	in: 11 x 35 cm: 27.9 x 88.9	1202	1202BEI	1202BLK	5 lbs./2.3 kg.
5 gal./18.9 L	in: 12 x 40 cm: 30.5 x 101.6	1205	1205BEI	1205BLK	7 lbs./3.2 kg.

Capacity	Dimensions	Original Butt Can		Weight
		Yellow	Beige	
5 gal./18.9 L	in: 12 x 33 cm: 30.5 x 83.8	1200YELLOW	1200BEIGE	7 lbs./3.2 kg.

Model	Description	Dimensions	Decorative SafeSmoker™		Weight
			Capacity	Weight	
1212BLACK	SafeSmoker™-Hitching Post	in: 12½ x 44½ cm: 31.8 x 111.8	2 gal./7.58 L	18 lbs./8.2 kg.	
1213BLACK	SafeSmoker™-Classic	in: 12½ x 37 cm: 31.8 x 94	2 gal./7.58 L	18 lbs./8.2 kg.	

**1206BLACK**  
5 qt./4.7 L  
in: 15¼ x 37¼ cm: 38.8 x 95.9

**1208BLACK**  
4 gal./15.2 L  
in: 17¼ x 43¼ cm: 43.8 x 109.9

**1213BLACK**  
2 gal./7.58 L  
in: 12½ x 37 cm: 31.8 x 94

Container top removes easily to empty internal galvanized steel bucket.

